

## DHI-LM32-B200

32" FHD Monitor



## Features:

- · Light and cost-effective plastic housing
- · suitable for continuous 24/7 operation
- $\cdot$  178°H/178°V extra-wide viewing angle for overall viewing performance
- · High fidelity digital processing for a brilliant and vivid video
- · 8ms fast response time with no image blurring or ghosting
- · Support multiple signal inputs such as HDMI and VGA
- · Low energy consumption, long service life









Technical Specification		
Model		
Model	DHI-LM32-B2000	
Display		
Screen Size	31.5"	
Aspect Ratio	16:9	
Resolution	1920×1080 (FHD)	
Backlight	LED	
Brightness/Luminance	250 cd/ m²	
Contrast	1400:1	
Display Color	16.7M(8bit)	
Viewing Angle(H/V)	178°(H)/178°(V)	
Response time	8ms	
Refresh Rate	60Hz	
Signals		
Input	VGA×1, HDMI×1,	
General		
Power Supply	AC100~240V (+/-10%), 50/60 Hz	

Consumption (Standard)	40W			
Consumption (Standby)	≤0.5W			
Net Weight	5.1Kg			
Gross Weight	7.5Kg			
Wall Mount	100×100mm			
Dimension without standard (W×H×D)	714.97*189.2*507.41mm			
Package(W×H×D)	784*142*497mm			
Work Environment	Temperature	0℃~40℃ (32°F~104°F)		
work environment	Humidity	10%~85%		
Accessory				
Standard	HDMI cable, power cable, pedestal			
Optional	Hanging bracket			
Certifications				
Certifications	CE/FCC			

## Commercial Series | DHI-LM32-B200

## Dimensions(mm)

