

45 Degree Weaver/Picatinny Mount

USER MANUAL

Mount type	Weaver/Picatinny
Material	Aluminum
Finish	Matte black
Length (mm)	55.2
Width (mm)	39.5
Height (mm)	21.8
Weight (oz)	1.8

Included Accesories:

Allen wrench

Features:

- Allows attachment of flashlight, lasers, micro reflex sights and red dots
- Offset design prevents mounted accessories from interfering with main optic
- Lightweight, durable aluminum construction

Installation

Installation Instructions:

- 1. Before you begin, check to make sure the weapon is unloaded.
- 2. Loosen the two mounting bolts on the Firefield 45 degree mount with the provided Allen wrench.
- 3. Attach the 45 degree mount to the mount of a quad rail or upper receiver. Tighten the bolts between 45-65 pounds of torque. Do not over tighten.

Troubleshooting

Never ship back a product without getting proper authorization beforehand. Doing so could result in losing the product due to a multitude of reasons, i.e. sending it to the wrong address and other problems associated with unexpected packages.

I. If sight does not hold zero, check that the mount is securely attached. Also verify the weapon sight is mounted securely. If there is any shifting, retighten the mounting system according to the mounting onstructions but do not over tighten.

Firefield Warranty

Please visit www.fire-field.com for warranty details and information.